



E AND J TECHNOLOGY GROUP CO LTD

Web: www.enjpower.com Email: sales@ejtechgroup.com

Active Battery BMS, Active Battery Balancer, Battery Monitors/SOC display, Customized Battery Pack

EJBMS For Business Customers(Support PC Software)

Model	String Range	Continuous discharge current	Maximum discharge	Equalizing current
EJBMS2A4S100SP	4	100A	400A	0-2A
EJBMS2A4S200SP	4	200A	800A	0-2A
EJBMS2A4S250SP	4	250A	800A	0-2A
EJBMS2A16S100	5-16	100A	400A	0-2A
EJBMS2A16S200	5-16	200A	800A	0-2A
EJBMS2A16S100P	5-16	100A	400A	0-2A
EJBMS2A16S200P	5-16	200A	800A	0-2A
EJBMS2A16S600R	5-16	600A	1200A	0-2A
EJBMS2A16S100LP	5-16	100A	400A	0-2A
EJBMS2A16S200LP	5-16	200A	800A	0-2A
EJBMS2A24S100	5-24	100A	400A	0-2A
EJBMS2A24S200	5-24	200A	800A	0-2A
EJBMS2A24S100P	5-24	100A	400A	0-2A
EJBMS2A24S200P	5-24	200A	800A	0-2A
EJBMS2A4SR	4	600A	1200A	0-2A
EJBMS2A16SR	5-16	600A	1200A	0-2A
EJBMS2A24SR	5-24	600A	1200A	0-2A

Active Equalizer

Model	String	Equalizing current	Power supply range
EJBL2A4S	4	0-2A	Battery power
EJBL2A16S	5-16	0-2A	Battery power
EJBL2A24S	5-24	0-2A	Battery power

EJBMS SP Series: Support 4pcs series and no limitation for parallel

EJBMS P Series: Support 16Pcs In parallel

EJBMS LP Series: Support 16Pcs In parallel, LP for 2U/3U/4U home energy storage battery packs.

EJBMS R Series: Relay Type BMS

EJBMS SR Series: Master-Slave series version high voltage BMS Series support up to 1500V

Communication type: Bluetooth is default, Optional: CANBus, RS485, RS232, LCD Display